

# **Mannering Colliery**

## **Monthly attended noise monitoring - January 2023**

---

Prepared for Great Southern Energy Pty Ltd (trading as Delta Coal)

February 2023

# Mannering Colliery

## Monthly attended noise monitoring - January 2023

Great Southern Energy Pty Ltd (trading as Delta Coal)

E220750 RP1

February 2023

Version	Date	Prepared by	Approved by	Comments
1	30 January 2023	Teanuanua Villierme	Najah Ishac	Draft
2	6 February 2023	Teanuanua Villierme	Najah Ishac	Final

Approved by



**Najah Ishac**

Director, Technical Lead Acoustics

6 February 2023

Level 3 175 Scott Street

Newcastle NSW 2300

This report has been prepared in accordance with the brief provided by Great Southern Energy Pty Ltd (trading as Delta Coal) and, in its preparation, EMM has relied upon the information collected at the times and under the conditions specified in this report. All findings, conclusions or recommendations contained in this report are based on those aforementioned circumstances. The contents of this report are private and confidential. This report is only for Great Southern Energy Pty Ltd (trading as Delta Coal) use in accordance with its agreement with EMM and is not to be relied on by or made available to any other party without EMM's prior written consent. Except as permitted by the *Copyright Act 1968* (Cth) and only to the extent incapable of exclusion, any other use (including use or reproduction of this report for resale or other commercial purposes) is prohibited without EMM's prior written consent. Except where expressly agreed to by EMM in writing, and to the extent permitted by law, EMM will have no liability (and assumes no duty of care) to any person in relation to this document, other than to Great Southern Energy Pty Ltd (trading as Delta Coal) and subject to the terms of EMM's agreement with Great Southern Energy Pty Ltd).

© EMM Consulting Pty Ltd, Ground Floor Suite 01, 20 Chandos Street, St Leonards NSW 2065. 2023.

# TABLE OF CONTENTS

---

<b>1</b>	<b>Introduction</b>	<b>1</b>
<b>2</b>	<b>Noise limits</b>	<b>2</b>
2.1	Overview	2
2.2	Noise limits	2
2.3	Adjustment to noise limits under certain meteorological conditions	2
2.4	Modifying factors	3
<b>3</b>	<b>Assessment methodology</b>	<b>4</b>
3.1	Attended noise monitoring	4
3.2	Instrumentation	4
3.3	Determination of stability categories	6
<b>4</b>	<b>Review of data and discussion</b>	<b>7</b>
<b>5</b>	<b>Conclusion</b>	<b>9</b>
	<b>References</b>	<b>10</b>

## Appendices

Appendix A	Glossary of acoustic terms	A.1
Appendix B	Project approval extract	B.1
Appendix C	EPL extract	C.1
Appendix D	Calibration certificates	D.1

## Tables

Table 2.1	Attended noise monitoring locations and noise limits	2
Table 3.1	Attended noise monitoring locations	4
Table 3.2	Stability categories and temperature lapse rates	6
Table 4.1	MC attended noise monitoring results – January 2023	8
Table A.1	Glossary of acoustic terms	A.2
Table A.2	Perceived change in noise	A.3

## Figures

Figure 3.1	Attended noise monitoring and assessment locations	5
Figure A.1	Common noise levels	A.3

# 1 Introduction

EMM Consulting Pty Limited (EMM) was engaged to complete operator-attended noise surveys on behalf of Great Southern Energy Pty Ltd (Delta Coal).

The purpose of the monitoring was to address requirements of the approved Mannering Colliery Noise Management Plan (NMP), prepared to satisfy the requirements of the project approval MP06\_0311 (PA) and Environment Protection License (EPL) 191. The NMP incorporates noise management for both Delta Coal's Chain Valley Colliery (CVC) and Mannering Colliery (MC).

Noise monitoring is required to occur monthly for MC. This report presents the results and findings of attended noise monitoring conducted on 16 January 2023.

The following material was referenced as part of this assessment:

- Department of Planning, Industry and Environment (DPE), PA MP06\_0311, as modified on 5 June 2020 (current as of the monitoring date 16 January 2023);
- Environment Protection Authority (EPA), EPL 191, as varied on 14 April 2021 (current as of the monitoring date 16 January 2023);
- NSW EPA, Noise Policy for Industry (NPfI), 2017; and
- Chain Valley Colliery and Mannering Colliery Noise Management Plan (approved 19 April 2022) updated following MC Mod 5 approval (Mod 5 approval).

A glossary of acoustic terms relevant to this report is provided in Appendix A.

## 2 Noise limits

### 2.1 Overview

Noise limits for MC are provided in Table 1, Condition 2 of Schedule 3 of the PA. The EPL references the PA with respect to noise limits. Extracts of the relevant sections of the PA and EPL pertaining to noise are provided in Appendix B and Appendix C, respectively.

The NMP was prepared in line with the Mod 5 approval and in accordance with the NPfI. Three attended noise monitoring locations representative of the PA noise assessment locations have been adopted in the NMP for the purpose of determining compliance with relevant noise limits.

### 2.2 Noise limits

The MC attended noise monitoring program is undertaken monthly during the evening and night periods. The attended noise monitoring locations and relevant limits per the NMP are summarised in Table 2.1.

**Table 2.1** Attended noise monitoring locations and noise limits

Attended noise monitoring location	Assessment locations	Day $L_{Aeq,15min}$ , dB	Evening $L_{Aeq,15min}$ , dB	Night $L_{Aeq,15min}$ , dB	Night $L_{A1,1min}$ , dB
RA1	4, 5, 6	40	36	36	46
RA2	7, 8	40	40	40	45
RA3	9, 11, 18, 20	40	39	39	49

For this assessment, the measured  $L_{Amax}$  has been used as a conservative estimate of  $L_{A1,1min}$ . The EPA accepts sleep disturbance analysis based on either the  $L_{A1,1min}$  or  $L_{Amax}$  metrics, with the  $L_{Amax}$  resulting in a more conservative assessment of site noise emissions.

### 2.3 Adjustment to noise limits under certain meteorological conditions

The PA (Mod 5) states the following:

Noise generated by the development must be monitored and measured in accordance with the relevant procedures and exemptions (including certain meteorological conditions) of the NSW Noise Policy for Industry (EPA, 2017).

Section 5.2 of the NPfI states that noise limits applicable under 'very noise-enhancing' conditions should be the limits that apply under 'standard' or 'noise-enhancing' conditions plus 5 dB. This implies that there will be no periods when noise limits do not apply due to meteorological conditions. Refer the glossary of acoustic terms in Appendix A for the definition of 'standard', 'noise-enhancing' and 'very noise -enhancing' meteorological conditions.

As per the PA (Mod 5) and NMP, and in accordance with the NPfI, this assessment has adopted a +5 dB adjustment to the limits shown in Table 2.1 when monitoring is undertaken during the following 'very noise-enhancing' conditions:

- wind speeds greater than 3 m/s at 10 m above ground level;

- stability category F temperature inversion conditions with wind speeds greater than 2 m/s at 10 m above ground level; or
- stability category G temperature inversion conditions.

When monitoring has been undertaken during 'very noise-enhancing' conditions and a +5 dB adjustment to the limits has been adopted, this is indicated in Table 4.1.

## 2.4 Modifying factors

The NPfI was approved for use in NSW in October 2017. For assessment of modifying factors, the NPfI immediately superseded the 'Industrial Noise Policy' (INP 2000), as outlined in the EPA document 'Implementation and transitional arrangements for the Noise Policy for Industry (2017)'. Assessment and reporting of modifying factors has been undertaken in accordance with Fact Sheet C of the NPfI.

## 3 Assessment methodology

### 3.1 Attended noise monitoring

To quantify noise emissions from MC, 15-minute operator-attended noise monitoring surveys were completed at three representative locations as per the NMP.

Attended noise monitoring locations and their coordinates are listed in Table 3.1 and are shown in Figure 3.1.

**Table 3.1** Attended noise monitoring locations

Attended noise monitoring location	Description	Coordinates (MGA56)	
		Easting	Northing
RA1	Pacific Highway, Doyalson	364646	6327221
RA2	Macquarie Shores Home Village, Doyalson North	365164	6328332
RA3	Tall Timbers Road (northern end), Kingfisher Shores	365069	6328953

The attended noise monitoring consisted of two 15-minute operator-attended noise monitoring measurements at each of the monitoring locations (ie RA1, RA2 and RA3); one during the evening and one during the night period in accordance with methodology outlined in the NMP.


As per the NMP, attended noise monitoring is scheduled considering the occurrence of regular operations at MC. Noise monitoring is generally planned to avoid scheduled down-time or maintenance. Regular operations (ie coal production) were occurring during the monitoring period.

### 3.2 Instrumentation

One Brüel & Kjær 2250 Type 1 sound analyser (s/n 2759405) was used to conduct 15-minute attended measurements and record one-third octave frequency and statistical noise indices. The sound analyser was calibrated before and on completion of the measurements using a Svantek SV-36 sound level calibrator (s/n 79952). Instrumentation calibration certificates are provided in Appendix D.

Where possible throughout each measurement the operator has quantified the contribution of site noise and other significant noise sources. This was done by matching audible sounds with the response of the sound analyser (where applicable) and/or via post-analysis of data (eg low-pass filtering).





Source: EMM (2021); NearMap (2019); DFSI (2017)

## KEY

- ▮ Manning Colliery project approval boundary
- ▮ Alignment of overland conveyor to VPPS
- ▮ Main road
- ▮ Local road
- ▮ Watercourse/drainage line
- ▮ Waterbody
- ▮ Cadastral boundary

- Assessment location
- Attended monitoring location
- ▲ Continuous monitoring location
- ▲ Meteorological station

Attended noise monitoring  
and assessment locations

Manning Colliery  
Figure 3.1



### 3.3 Determination of stability categories

For this assessment and as required by the NMP, atmospheric stability categories were determined for each 15-minute attended monitoring period. The stability category data (calculated from sigma-theta data) as well as the average wind data (speed and direction) for the monitoring period were obtained from MC's weather station located to the north of the site (refer to Figure 3.1).

The stability categories and associated ranges in temperature lapse rates are presented in Table 3.2.

**Table 3.2**      **Stability categories and temperature lapse rates**

Stability category	Temperature lapse rate ( $\Delta T$ ) ( $^{\circ}\text{C}/100\text{ m}$ )
A	$\Delta T < -1.9$
B	$-1.9 \leq \Delta T < -1.7$
C	$-1.7 \leq \Delta T < -1.5$
D	$-1.5 \leq \Delta T < -0.5$
E	$-0.5 \leq \Delta T < 1.5$
F	$1.5 \leq \Delta T < 4.0$
G	$\Delta T \geq 4.0$

Source:    NPfl (EPA 2017).

## 4 Review of data and discussion

Results of attended noise measurements are summarised in Table 4.1. Noise from MC was quantified for each survey using in-field observations and post-analysis of data as required (eg removing higher frequencies that are not mine related where applicable).

Attended noise monitoring was completed during the evening and night periods on 16 January 2023. A total of six 15-minute operator-attended noise measurements were undertaken for this round of monthly (January 2023) noise monitoring; results for those are presented in Table 4.1.

Meteorological data for the monitoring period was sourced from MC's weather station to determine relevant noise limits in accordance with the NMP. In accordance with the NMP, the standard noise limits applied for all six 15-minute attended noise measurements.

Site noise was inaudible during all six measurements. Typically, when a particular source is not audible above local ambient noise levels, the likely contribution of that source is at least 10 dB below the measured background ( $L_{A90}$ ) level. For most of the measurements, the measured  $L_{A90,15min}$  noise level was no greater than 10 dB above the applicable  $L_{Aeq,15min}$  limit. Given this, it is expected that the site  $L_{Aeq,15min}$  noise levels were below the relevant noise limits for those measurements. For the evening period measurement at RA1, the measured  $L_{A90,15min}$  noise level was greater than 10 dB above the applicable  $L_{Aeq,15min}$  limit. The background noise level ( $L_{A90,15min}$ ) during this measurement was observed to be heavily influenced by noise from road traffic on the Pacific Highway. It is expected that site noise levels would have been at or below the relevant noise limits at this location. Therefore, site noise levels are considered to have complied with relevant noise limits at all locations.

Measured site-only levels were assessed for the applicability of modifying factors in accordance with the NPfI (refer to Section 2.4). There were no modifying factors applicable, as defined in the NPfI, during the survey.

Noise levels from MC ( $L_{Aeq,15min}$  and  $L_{Amax}$ ) were determined to have been less than relevant noise limits at all locations for this round of noise monitoring, as per the NMP.

**Table 4.1**      **MC attended noise monitoring results – January 2023**

Location	Date	Start time (hours)	Total 15-minute noise levels, dB						Site levels, dB			Met. conditions <sup>3</sup> Very noise-enhancing?	Applicable noise limits, dB		Exceedance, dB	Comments
			L <sub>Amin</sub>	L <sub>A90</sub>	L <sub>Aeq</sub>	L <sub>A10</sub>	L <sub>A1</sub>	L <sub>Amax</sub>	Mod. factor <sup>1</sup>	L <sub>Aeq</sub>	L <sub>Amax</sub> <sup>2</sup>		L <sub>Aeq</sub>	L <sub>Amax</sub> <sup>2</sup>		
RA1	16/1	20:55 (Eve.)	38	47	59	63	68	73	N/A	IA	N/A	0.4 m/s 120° SC F No	36	N/A	Nil	<b>MC inaudible.</b> Traffic on the Pacific Highway consistently audible. Insects consistently audible. Vales Point Power Station (VPPS) hum audible in the background.
RA3	16/1	21:15 (Eve.)	36	39	43	45	47	56	N/A	IA	N/A	0.6 m/s 102° SC F No	39	N/A	Nil	<b>MC inaudible.</b> VPPS hum consistently audible (dominant). Insects consistently audible.
RA2	16/1	21:45 (Eve.)	32	35	38	38	43	66	N/A	IA	N/A	0.4 m/s 97° SC F No	40	N/A	Nil	<b>MC inaudible.</b> VPPS hum consistently audible (dominant). Insects consistently audible. Distant traffic occasionally audible. Aircraft noise briefly audible. Residents nearby talking.
RA1	16/1	22:09 (Night)	35	40	56	60	65	72	N/A	IA	IA	0.4 m/s 159° SC F No	36	46	Nil	<b>MC inaudible.</b> Traffic on the Pacific Highway consistently audible. Insects consistently audible. VPPS hum audible in the background.
RA3	16/1	22:30 (Night)	34	37	42	46	48	54	N/A	IA	IA	0.4 m/s 111° SC F No	39	49	Nil	<b>MC inaudible.</b> VPPS hum consistently audible (dominant). Insects consistently audible. Traffic on Tall Timbers Road audible once.
RA2	16/1	23:00 (Night)	32	34	35	37	38	48	N/A	IA	IA	0.5 m/s 133° SC F No	40	45	Nil	<b>MC inaudible.</b> VPPS hum consistently audible (dominant). Insects consistently audible. Distant traffic occasionally audible.

- Notes:
1. Modifying factor in accordance with Fact sheet C of the NPfl (refer to Section 2.4).
  2. For assessment purposes the recorded L<sub>Amax</sub> has been used as a conservative estimate of the L<sub>A1,1min</sub>.
  3. Meteorological data including wind speed, wind direction and stability category (SC) were taken as an average over 15 minutes from MC weather station (refer to Section 3.3).
  4. IA = inaudible.
  5. N/A = not applicable.



## 5 Conclusion

EMM has completed a review of mine noise from MC within the surrounding community based on attended measurements conducted on 16 January 2023.

Meteorological data for the monitoring period was sourced from MC's weather station to determine relevant noise limits in accordance with the approved NMP. In accordance with the NMP, the standard noise limits applied for all six 15-minute attended noise measurements.

The assessment of noise from site included consideration of modifying factors for certain noise characteristics, such as low frequency noise, in accordance with the NPfI. Modifying factors were found to be not applicable at all monitoring locations.

Noise levels from MC were below relevant noise limits at all monitoring locations as per the NMP.

## References

Chain Valley Colliery and Mannering Colliery Noise Management Plan, 2022.

NSW Department of Planning, Industry and Environment, Project Approval MP 06\_0311, 2020.

NSW Environment Protection Authority, Environment Protection License 191, 2021.

NSW Environment Protection Authority, Industrial Noise Policy, 2000.

NSW Environment Protection Authority, Noise Policy for Industry, 2017.

NSW Environment Protection Authority, Implementation and transitional arrangements for the Noise Policy for Industry (2017), 2017.

---

# Appendix A

## Glossary of acoustic terms

---



Several technical terms are discussed in this report. These are explained in Table A.1.


**Table A.1**      **Glossary of acoustic terms**

Term	Description
dB	Noise is measured in units called decibels (dB). There are several scales for describing noise, the most common being the 'A-weighted' scale. This attempts to closely approximate the frequency response of the human ear.
L <sub>A1</sub>	The 'A-weighted' noise level which is exceeded 1% of the time.
L <sub>A1,1min</sub>	The 'A-weighted' noise level exceeded for 1% of the specified period of 1 minute.
L <sub>A10</sub>	The 'A-weighted' noise level which is exceeded 10% of the time.
L <sub>A90</sub>	Commonly referred to as the background noise level. The 'A-weighted' noise level exceeded 90% of the time.
L <sub>Aeq</sub>	The energy average noise from a source. This is the equivalent continuous 'A-weighted' sound pressure level over a given period. The L <sub>Aeq,15min</sub> descriptor refers to an L <sub>Aeq</sub> noise level measured over a 15-minute period.
L <sub>Amin</sub>	The minimum 'A-weighted' noise level received during a measuring interval.
L <sub>Amax</sub>	The maximum root mean squared 'A-weighted' sound pressure level (or maximum noise level) received during a measuring interval.
Day period	Monday – Saturday: 7 am to 6 pm, on Sundays and Public Holidays: 8 am to 6 pm.
Evening period	Monday – Saturday: 6 pm to 10 pm, on Sundays and Public Holidays: 6 pm to 10 pm.
INP	Industrial Noise Policy (EPA 2000).
NPfl	Noise Policy for Industry (EPA 2017).
Standard meteorological conditions	Stability categories A-D with wind speed up to 0.5 m/s at 10 m above ground level during the day, evening, or night period, as defined in Table D1 of the NPfl.
Noise-enhancing meteorological conditions	Stability categories A-D with wind speed up to 3 m/s at 10 m above ground level during the day, evening, or night period, or stability category F with wind speed up to 2 m/s at 10 m above ground level during the night period, as defined in Table D1 of the NPfl. This does not necessarily imply that meteorological conditions were enhancing site noise at the monitoring location.
Very noise-enhancing meteorological conditions	Meteorological conditions outside of the range of either standard or noise-enhancing meteorological conditions, as defined in the NPfl. This does not necessarily imply that meteorological conditions were enhancing site noise at the monitoring location.
Night period	Monday – Saturday: 10 pm to 7 am, on Sundays and Public Holidays: 10 pm to 8 am.
Temperature inversion	A meteorological condition where the atmospheric temperature increases with altitude.

It is useful to have an appreciation of the decibel (dB), the unit of noise measurement. Table A.2 gives an indication as to how an average person perceives changes in noise level in the environment. Examples of common noise levels are provided in Figure A.1.

**Table A.2**      **Perceived change in noise**

Change in sound pressure level (dB)	Perceived change in noise in surrounding environment
up to 2	not perceptible
3	just perceptible
5	noticeable difference
10	twice (or half) as loud
15	large change
20	four times (or quarter) as loud



**Figure A.1**      **Common noise levels**

---

# Appendix B

## Project approval extract

---



## SCHEDULE 3 SPECIFIC ENVIRONMENTAL CONDITIONS

### NOISE

#### Construction Noise

1. The Applicant must ensure that the noise generated by any construction work is managed in accordance with the requirements outlined in the *Interim Construction Noise Guideline* (DECC, 2009).

#### Operational Noise Criteria

2. Except for the carrying out of construction works, the Applicant must ensure that the noise generated by the development does not exceed the criteria in Table 1 at any residence<sup>a</sup> on privately-owned land.

**Table 1:** Operational noise criteria dB(A)

Noise Assessment Location	Day <i>L<sub>Aeq</sub></i> (15 min)	Evening <i>L<sub>Aeq</sub></i> (15 min)	Night <i>L<sub>Aeq</sub></i> (15 min)	Night <i>L<sub>A1</sub></i> (1 min)
4 – di Rocco	40	36	36	46
5 - Keighran	40	39	39	49
6 – Swan	40	37	37	47
7 – Druitt	40	35	35	45
8 – Macquarie Shores Home Village	42	42	42	47
9 - Jeans	40	37	37	47
11 - Jeans	40	36	36	46
18 - Jeans	40	36	36	46
20 – Knight and all other privately-owned residences	40	36	36	46

<sup>a</sup> The Noise Assessment Locations referred to in Table 1 are shown in Appendix 4.

Noise generated by the development must be monitored and measured in accordance with the relevant procedures and exemptions (including certain meteorological conditions) of the *NSW Noise Policy for Industry* (EPA, 2017).

3. The noise criteria in Table 1 do not apply if the Applicant has an agreement with the owner/s of the relevant residence or land to exceed the noise criteria, and the Applicant has advised the Department in writing of the terms of this agreement.

#### Noise Operating Conditions

- 3A. The Applicant must:
  - (a) take all reasonable steps to minimise noise from construction and operational activities, including low frequency noise and other audible characteristics, associated with the development;
  - (b) implement reasonable and feasible noise attenuation measures on all plant and equipment that will operate in noise sensitive areas;
  - (c) operate a comprehensive noise management system commensurate with the risk of impact;
  - (d) take all reasonable steps to minimise the noise impacts of the development during noise-enhancing meteorological conditions when the noise criteria in this consent do not apply (see NPfI);
  - (e) carry out regular attended noise monitoring (at least once a month, unless otherwise agreed by the Planning Secretary) to determine whether the development is complying with the relevant conditions of this consent;

- (f) regularly assess the noise monitoring data and modify or stop operations on the site to ensure compliance with the relevant conditions of this consent; and
  - (g) implement reasonable and feasible measures to further enclose the structure housing the coal crusher in order to further mitigate noise from operational activities.
- 3B. The Applicant must decommission the surface rotary breaker identified in the Statement of Commitments at Appendix 3, within 3 months of approval of Modification 5.

#### Noise Management Plan

- 3C. The Applicant must prepare a Noise Management Plan for the development to the satisfaction of the Planning Secretary. This plan must:
- (a) be prepared by a suitably qualified and experienced person/s whose appointment has been endorsed by the Planning Secretary;
  - (b) describe the measures to be implemented to ensure:
    - i. compliance with the noise criteria and operating conditions in this consent;
    - ii. best practice management is being employed; and
    - iii. noise impacts of the development are minimised during noise-enhancing meteorological conditions when the noise criteria in this consent do not apply (see NPfI);
  - (c) describe the noise management system in detail; and
  - (d) include a monitoring program that:
    - i. uses a combination of real-time and supplementary attended monitoring to evaluate the performance of the development;
    - ii. monitors noise at the nearest and/or most affected residences;
    - iii. includes a program to calibrate and validate the real-time noise monitoring results with the attended monitoring results over time;
    - iv. adequately supports the noise management system;
    - v. includes a protocol for distinguishing noise emissions of the development from any neighbouring developments; and
    - vi. includes a protocol for identifying any noise-related exceedance, incident or non-compliance and for notifying the Department and relevant stakeholders of any such event.

The Applicant must implement the Noise Management Plan as approved by the Planning Secretary.

#### SUBSIDENCE

4. The Applicant must limit its coal extraction methods on the site to first workings only, and must not undertake second workings.
5. Deleted.

#### SOIL AND WATER

##### Discharge

6. The Applicant must only discharge water from the site as expressly provided for by its EPL.
7. The Applicant must investigate, assess and report on the ecological interactions of minewater discharged from the site with the aquatic ecology of the unnamed creek and wetlands (and associated vegetation) between the minewater discharge point/s and Lake Macquarie. This report must:
- (a) be prepared in consultation with EPA by suitably qualified expert/s whose appointment/s have been approved by the Planning Secretary;
  - (b) be submitted to the Planning Secretary by the end of March 2009; and
  - (c) assess the probable alterations in the local ecology attributable to previous and proposed minewater discharges and any future cessation of minewater discharge flows.

#### Water Management Plan

8. The Applicant must prepare a Water Management Plan for the development to the satisfaction of the Planning Secretary. This plan must:
- (a) be prepared in consultation with DPIE Water by suitably qualified expert/s whose appointment/s have been approved by the Planning Secretary;
  - (b) be submitted the Planning Secretary by the end of March 2009; and
  - (c) include a:
    - Site Water Balance;

---

# Appendix C

## EPL extract

---



# Environment Protection Licence

Licence - 191

- L4.1 The licensee must not cause, permit or allow any waste to be received at the premises, except the wastes expressly referred to in the column titled “Waste” and meeting the definition, if any, in the column titled “Description” in the table below.

Any waste received at the premises must only be used for the activities referred to in relation to that waste in the column titled “Activity” in the table below.

Any waste received at the premises is subject to those limits or conditions, if any, referred to in relation to that waste contained in the column titled “Other Limits” in the table below.

This condition does not limit any other conditions in this licence.

Code	Waste	Description	Activity	Other Limits
NA	Waste	Any other waste received on the premises for storage, treatment, processing, sorting or disposal and which receipt is not a scheduled activity under Schedule 1 of the POEO Act, as in force from time to time.		
NA	General or Specific exempted waste	Waste that meets all the conditions of a resource recovery exemption under Clause 51A of the Protection of the Environment Operations (Waste) Regulation 2014	As specified in each particular resource recovery exemption	N/A

- L4.2 The licensee must not cause, permit or allow any waste generated outside the premises to be received at the premises for storage, treatment, processing, reprocessing or disposal or any waste generated at the premises to be disposed of at the premises, except as expressly permitted by the licence.
- L4.3 This condition only applies to the storage, treatment, processing, reprocessing or disposal of waste at the premises if it requires an environment protection licence.

## L5 Noise limits

Note: Noise limits are not specified as a condition of this licence. Noise limits are prescribed with the conditions of Project Approval 06\_0311 granted under the *Environmental Planning and Assessment Act 1979*. Under the *Environmental Planning and Assessment Act 1979* the Department of Planning is the appropriate authority in respect of the administration and regulation of the Project Approval.

## 4 Operating Conditions

### O1 Activities must be carried out in a competent manner

- O1.1 Licensed activities must be carried out in a competent manner.

---

## Appendix D

### Calibration certificates

---

# CERTIFICATE OF CALIBRATION

CERTIFICATE No: **C33872**

EQUIPMENT TESTED : Sound Level Calibrator

Manufacturer: Svantek

Type No: SV-36 Serial No: 79952

Owner: EMM Consulting Pty Ltd  
L3, 175 Scott Street  
Newcastle, NSW 2300

Tests Performed: Measured Output Pressure level, Frequency & Distortion

Comments: See Details overleaf. All Test Passed.

Parameter	Pre-Adj	Adj Y/N	Output: (dB re 20 $\mu$ Pa)	Frequency (Hz)	THD&N (%)
Level1:	NA	N	94.09 dB	1000.00 Hz	1.12 %
Level2:	NA	N	114.06 dB	1000.00 Hz	0.71 %
Uncertainty			$\pm 0.11$ dB	$\pm 0.05\%$	$\pm 0.20$ %
Uncertainty (at 95% c.i.) k=2					

## CONDITION OF TEST:

Ambient Pressure 1004 hPa  $\pm 1$  hPa  
Temperature 23  $^{\circ}\text{C} \pm 1^{\circ}\text{C}$   
Relative Humidity 55 %  $\pm 5\%$

Date of Receipt : 26/09/2022  
Date of Calibration : 29/09/2022  
Date of Issue : 29/09/2022

Acu-Vib Test AVP02 (Calibrators)

Procedure: Test Method: AS IEC 60942 - 2017

CHECKED BY:

AUTHORISED  
SIGNATURE:

  
Hein Soe

Accredited for compliance with ISO/IEC 17025 - Calibration

Results of the tests, calibration and/or measurements included in this document are traceable to SI units through reference equipment that has been calibrated by the Australian National Measurement Institute or other NATA accredited laboratories demonstrating traceability.

This report applies only to the item identified in the report and may not be reproduced in part.

The uncertainties quoted are calculated in accordance with the methods of the ISO Guide to the Uncertainty of Measurement and quoted at a coverage factor of 2 with a confidence interval of approximately 95%.



WORLD RECOGNISED  
ACCREDITATION

Accredited Lab No. 9262  
Acoustic and Vibration  
Measurements

**Acu-Vib Electronics**  
CALIBRATIONS SALES RENTALS REPAIRS

Head Office & Calibration Laboratory  
Unit 14, 22 Hudson Ave. Castle Hill NSW 2154  
(02) 9680 8133  
www.acu-vib.com.au



# CERTIFICATE OF CALIBRATION

CERTIFICATE No: **SLM31670**

EQUIPMENT TESTED: Sound Level Meter

Manufacturer: B & K  
Type No: 2250  
Mic. Type: 4189  
Pre-Amp. Type: ZC0032

Serial No: 2759405  
Serial No: 2983733  
Serial No: 22666

Filter Type: 1/3 Octave

Test No: F031671

Owner: EMM Consulting  
Level 3, 175 Scott Street  
Newcastle, NSW 2300

Tests Performed: IEC 61672-3:2013 & IEC 61260-3:2016


Comments: All Test passed for Class 1. (See overleaf for details)


## CONDITIONS OF TEST:

Ambient Pressure 992 hPa  $\pm 1$  hPa  
Temperature 26  $^{\circ}\text{C} \pm 1^{\circ}\text{C}$   
Relative Humidity 48 %  $\pm 5\%$

Date of Receipt: 02/02/2022  
Date of Calibration: 02/02/2022  
Date of Issue: 03/02/2022

Acu-Vib Test Procedure: AVP10 (SLM) & AVP06 (Filters)

CHECKED BY: 

AUTHORISED SIGNATURE: 

*Jack Kiehl*

Accredited for compliance with ISO/IEC 17025 - Calibration

Results of the tests, calibration and/or measurements included in this document are traceable to SI units through reference equipment that has been calibrated by the Australian National Measurement Institute or other NATA accredited laboratories demonstrating traceability.

This report applies only to the item identified in the report and may not be reproduced in part.

The uncertainties quoted are calculated in accordance with the methods of the ISO Guide to the Uncertainty of Measurement and quoted at a coverage factor of 2 with a confidence interval of approximately 95%.



WORLD RECOGNISED  
ACCREDITATION

Accredited Lab No. 9262  
Acoustic and Vibration  
Measurements

  
**Acu-Vib Electronics**  
CALIBRATIONS SALES RENTALS REPAIRS

Head Office & Calibration Laboratory  
Unit 14, 22 Hudson Ave. Castle Hill NSW 2154  
(02) 9680 8133  
[www.acu-vib.com.au](http://www.acu-vib.com.au)



## **Australia**

### **SYDNEY**

Ground floor 20 Chandos Street  
St Leonards NSW 2065  
T 02 9493 9500

### **NEWCASTLE**

Level 3 175 Scott Street  
Newcastle NSW 2300  
T 02 4907 4800

### **BRISBANE**

Level 1 87 Wickham Terrace  
Spring Hill QLD 4000  
T 07 3648 1200

### **CANBERRA**

Suite 2.04 Level 2  
15 London Circuit  
Canberra City ACT 2601

### **ADELAIDE**

Level 4 74 Pirie Street  
Adelaide SA 5000  
T 08 8232 2253

### **MELBOURNE**

Suite 8.03 Level 8  
454 Collins Street  
Melbourne VIC 3000  
T 03 9993 1900

### **PERTH**

Suite 9.02 Level 9  
109 St Georges Terrace  
Perth WA 6000  
T 08 6430 4800

## **Canada**

### **TORONTO**

2345 Young Street Suite 300  
Toronto ON M4P 2E5  
T 647 467 1605

### **VANCOUVER**

60 W 6th Ave Suite 200  
Vancouver BC V5Y 1K1  
T 604 999 8297



[linkedin.com/company/emm-consulting-pty-limited](https://www.linkedin.com/company/emm-consulting-pty-limited)



[emmconsulting.com.au](http://emmconsulting.com.au)